Organic-Inorganic Hybrids Consisted of 2D Nanosheets Materials


Prof. Shinobu UEMURA

Program in Advanced Materials Science, Faculty of Engineering and Design, Kagawa University.

HP: https://uemuragroup.wixsite.com/uemura-lab
https://www.researchgate.net/profile/Shinobu_Uemura


Preparation of Membranes Consisted of 2D Nanosheets for Desalinations

- ✓ **Freshwater crisis:** Decrease freshwater resources by climate change and decrease the availability of freshwater by growing world population.
- ✓ **Desalination of seawater:** Seawater comprises a vast supply of water (97.5% of all water on the earth).
- ✓ **Desalination techniques:** Desalination based on membranes is a primary technique due to their low energy consumption etc. Especially, reverse osmosis (RO) is the key technology for desalination.
- ✓ Commercial RO membrane: Thin-film composite polyamide
- ✓ **Challenges of RO membrane**: Low water permeability (required high pressure), and high fouling.



Typical RO membrane.

- > Strategy of our research: Composite membranes consisted of 2D nanosheets materials [Graphene oxide (GO)]
 - ♦ Easy preparation of single atomic layers
 - ♦ Hydrophilic (easy to disperse into aqueous solution)
 - ♦ Mechanically strength
 - ♦ Large area nanosheets
 - ◆ GO Layered films: Easy separation of each GO during the long-time immersion to water (in the desalination system)



Sustainable desalination membrane

[Carbon nitrides (CN)]

- ♦ Mechanically strength
- ♦ Similar chemical structures to GO: Intermolecular interaction between GO and CN
- ♦ Visible light responded photocatalysis
- ◆ Morphology control